DLG (Shanghai) Electronic Technology Co., LTD

Model: NCM18650-220 Document No.:SDS-0001-A.0

## SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** Lithium ion Battery

Model: NCM18650-220

Rated Capacity: 2200mAh

Nominal Voltage: 3.6V

Nominal Energy: 7.92Wh

Weight:  $44.0\pm2.0g$ 

**Revision Date: 2019-01-21** 

Company: DLG (Shanghai) Electronic Technology

Co., LTD

Address: Building 9, No.3492 Jinqian Road,

Fengxian District, Shanghai, China

Email: maggie1\_zhang@dlgbattery.cn

Fax: 0086 (21) 57475827

Tel: 0086 (21) 57475821

SDS Date: 2019-01-21

## **SECTION 2 HAZARDS IDENTIFICATION**

### **Hazards Identification:**

The battery has passed the items of UN model regulations, manual of test and criteria section UN 38.3

### **Emergency overview:**

Caution: avoid contact and inhalation the electrolyte contained inside the battery.

### **SECTION 3 INFORMATION ON INGREDIENTS**

DLG (Shanghai) Electronic Technology Co., LTD

Model: NCM18650-220 Document No.:SDS-0001-A.0

Product Name: Lithium ion Battery Model: NCM18650-220 Rated

Capacity: 2200mAh Nominal Voltage: 3.6V

Ingredient	Concentration	CAS No.
	(%)	
Cobalt lithium manganese	30~45	182442-95-1
nickel oxide		
Graphite	15~25	7782-42-5
Lithium hexaflurorphosphate	1~3	21324-40-3
(LiPF6)		
Copper foil	5~10	7440-50-8
Aluminum foil	2~8	7429-90-5
Steel, nickel and inert	0.5~5	9003-55-8
polymer		
Carbon black and others	0.5~2	1333-86-4
Poly (vinylidene fluoride)	0.1~2	24937-79-9
(PVDF)		

## **SECTION 4 FIRST AID MEASURES**

## Skin exposure:

If the internal battery materials of an opened battery cell come into contact with the skin, immediately flush with plenty water.

## Eye exposure:

In case of the internal battery materials in contact with eyes, flush with copious amounts of water for at least 15 minutes. Assure adequate flushing by separating the eyelids with fingers. Cell a physician.

DLG (Shanghai) Electronic Technology Co., LTD

Model: NCM18650-220 Document No.:SDS-0001-A.0

### Inhalation exposure:

If inhaled the internal materials of battery, remove immediately to fresh air and seek medical attention.

## **Oral exposure:**

If swallowed the internal materials of battery, do not induce vomiting. Seek immediate medical attention.

## **SECTION 5 FIRE-FIGHTING MEASURES**

### **Extinguishing media:**

Suitable: Dry chemical, Sandy soil, carbon dioxide or appropriate foam.

## Firefighting:

Protective Equipment: Wear self—contained breathing apparatus and protective clothing to with skin and eyes.

Specific hazards: Emit toxic fumes under fire conditions.

### SECTION 6 ACCIDENTAL RELEASE MEASURES

### **Procedure of Personal Precaution:**

If batteries show signs of leaking, avoid skin or eye contact with the material leaking from the battery. Use chemical resistant rubber gloves and non—flammable absorbent materials for clean up. Mix with inert material(e. g. dry sand, vermiculite) and transfer to sealed container for disposal.

## **SECTION 7 HANDLING AND STORAGE**

DLG (Shanghai) Electronic Technology Co., LTD

Model: NCM18650-220 Document No.:SDS-0001-A.0

## **Handling:**

Keep away from ignition sources, heat and flame. Such batteries must be packed in inner packages in such a manner as to effectively prevent short circuits and to prevent movement which could lead to short circuits. Avoid mechanical or electrical abuse. More than a momentary short circuit will generally reduce the battery service life. Avoid reversing battery polarity within the battery assembly. In case of a battery unintentionally be crushed, rubber gloves must be used to handle all battery components. Avoid contact with eyes, skin. Avoid inhalation. No smoking at working site. Materials to Avoid: Strong oxidizing agents, Corrosives.

### Storage:

Store in cool, well—ventilated area. Keep away from ignition sources, heat arid flame, Such batteries

must be packed in inner packages in such a manner as to effectively prevent short circuits and to prevent

movement which could lead to short circuits. Materials to Avoid: Strong oxidizing agents, Corrosives.

### **SECTION 8 EXPOSURE CONTROL/PPE**

### **Engineering Controls:**

Use ventilation equipment if available. Safety shower and eye bath.

### **Personal Protective Equipment:**

Respiratory System: Not necessary under conditions of normal use.

Eyes: Not necessary under conditions of normal use.

Clothing: Wear appropriate protective clothing.

Hand: Safety gloves.

#### Other Protect:

No smoking, drinking and eating at working site. Wash thoroughly after handling.

## **SECTION 9 PHYSICAL/CHEMICAL PROPERTIES**

DLG (Shanghai) Electronic Technology Co., LTD

Model: NCM18650-220 Document No.:SDS-0001-A.0

**Appearance**: Blue cylindrical plastics film shell

**Odor:** Odorless

Melting Point/°C: ≥300°C

Solubility: Partial slightly soluble in water

## **SECTION 10 STABILITY AND REACTIVITY**

## **Stability:**

Stable under normal temperatures and pressures.

### **Conditions to Avoid:**

Avoid exposure to heat and open flame. Avoid mechanical or electrical abuse.

Prevent movement which could lead to short circuits.

### **Materials to Avoid:**

Strong oxidizing agents, Corrosives.

### **Hazardous Polymerization:**

Will not occur.

### **Hazardous Decomposition Products:**

Metal oxides, CO, CO2.

## **SECTION 11 TOXICOLOGICAL INFORMATION**

## **Toxicity Data:**

Not available.

### **Irritation Data:**

The internal battery materials may cause irritation to eyes and skin.

## SECTION12 ECOLOGICAL INFORMATION

No data available.

### SECTION13 DISPOSAL CONSIDERATION

DLG (Shanghai) Electronic Technology Co., LTD

Model: NCM18650-220 Document No.:SDS-0001-A.0

## **Appropriate Method of Disposal of Substance:**

Lithium batteries are best disposed of as a non—hazardous waste when fully or mostly discharged. Contact a licensed professional waste disposal service to dispose of large quantities materials.

## SECTION14 TRANSPORT INFORMATION

The product has passed the test items of UN Model Regulations, Manual of Test and Criteria Section of UN 38.3 and UN Model Regulations, SP188, I. 2m drop test. The total net weight of the Lithium batteries is less than 10 kg.

## **TATA DGR (60th Edition):**

Proper Shipping Name: Lithium ion batteries

UN Number: UN3480

Hazard Class: 9

The product shall meet the General Requirements and section 1B of Packaging

Instruction 965 (IATA DGR).

## IMO IMDG Code (2019 Edition):

Shipping Name: not relevant Hazard Class: not relevant UN Number: not relevant Packing Group: not relevant.

The product is not restricted to IMO IMDG Code according to special provision

188.

## **SECTION 15 REGULATORY INFORMATION**

### ICAO:

1. Unless be exempted according to ICAO TI, the lithium ion cell/batteries (UN 3480, PI965) and lithium metal cell/batteries (UN 3090, PI 968) are forbidden for

DLG (Shanghai) Electronic Technology Co., LTD

Model: NCM18650-220 Document No.:SDS-0001-A.0

carriage on passenger aircraft.

- 2. Unless be approved according to ICAO TI, Lithium ion cells/batteries (UN 3480, PI 965) must be offered for transport at a state of charge (SoC) not exceeding 30% of their rated design capacity.
- 3. A shipper is not permitted to offer for transport more than one (I) package prepared according to Section II of PI 965 and PI 968 in any single consignment. Not more than one (I) package prepared in accordance with Section II of PI 965 and PI 968 may be placed into an overpack.
- 4. Packages prepared according to Section II of PI 965 and PI 968 must be offered to the operator separately from other cargo and must not be loaded into a unit load device (ULD) before being offered to the operator.

### SECTION16 OTHER INFORMATION

### Date:

2019-01-21

### **Revision:**

A.0

### Other Information:

The above information is based on the data of which we are aware and is believed to be correct as of the data hereof. Since this information may be applied under conditions beyond our control and with which may be unfamiliar and since data made available subsequent to the data hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.